

APO

Aluminum push out trailers are ideal for use in sludge hauling and similar material hauling applications.

Our aluminum push out trailers eject horizontally and are uniquely designed to safely haul and discharge sludge and other like materials. Because of their size and stability, our trailers allow owners and operators to haul maximum payload with less chance of rollover. They're constructed with top grade materials and come with many standard features and a wide variety of popular options.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 45 years of experience to build you the transfer trailer you want - we'll build it to your specification and application.

DYNAHAULER® SERIES

This trailer is engineered for municipal or commercial use.



ISO 9001:2000 Certified.
Quality products,
quality workmanship.

J&J Truck Bodies & Trailers is a division
of Somerset Welding & Steel, Inc.

**J&J TRUCK BODIES
& TRAILERS®**
Built for the Long Haul™

Call us today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR ALUMINUM PUSH OUTS

ALUMINUM STANDARD SPECIFICATIONS*

Side Panels: 3/16" 5454-H34 or 1/4".

Floor: 3/8" 5454-H34.

Top Rail: 9" extruded boxed channel 6061-T6.

Bottom Rail: 4" extruded bottom rail 6061-T6.

Side Posts: Extruded vertical posts 5/32" x 3 3/4" wide 6061-T6

Understructure: 4" x 4" extruded boxed channel crossmembers on 12" centers. Dual frame running full length of trailer consisting of (2) 7 "T" section long members interlocked with crossmembers. Welded directly to trailer floor. Crossmember on 12" centers.

Fifth Wheel Assembly: 3/8" steel plate, 2" SAE King Pin.

Ejector: 1/4" face plate backed by rigid brace members to withstand discharge thrust. UHMW Guide shoes top, bottom, and sides. Self-adjusting UHMW wipers on sides and bottom.

Ejector Hydraulic System: Ejector ram cylinder sized to completely unload the trailer. 9" diameter, 5 stage standard 3-line system, tank on tractor, dump valve on trailer for fast retraction.

Rear Door: Barn door, top hinged or hydraulic operated. Full seals available for sludge applications.

Suspension: REYCO 21B 52,000# four spring system with cast hangers.

Hubs: Steel hub piloted.

Wheels: 24.5" x 8.25" steel hub piloted.

Tires: 11R24.5 14 ply

Axles: Dana D-22 25,000# with 16 1/2" x 7" brakes.

Lighting: Truck-Lite® shock proof, harness system.

Landing Gear: Holland Mark V 2-speed with sand shoes. 50,000# lift, 180,000# static load capacity.

Other Standard Features: Mud guards, mud flaps, ladders, and tarp rails.



Front cow's nest with ladder optional. Controls can be mounted at top of bulkhead.



Ejector ram cylinder sized to completely unload trailer. Self-adjusting UHMW wipers on sides and bottom.



4" x 4" extruded boxed channel crossmembers. T-section longmembers running full length of trailer.

*Standard specifications may vary according to customer preferences and requirements. Many options are also available. At J&J, we can custom build to suit your needs.



Barn door, top hinged, or hydraulic operated rear doors with full seals available.



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:



Built for the Long Haul™

P.O. Box 735
10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 1+814.443.2671
Fax: 1+814.443.2621
Toll Free: 1+800.777.2671 (USA only)
Email: sales@jjbodies.com
www.jjbodies.com